



Features

- PC+ABS material shell with PMMA panel design
- Equipped with the 32-bit high-speed processor
- Built-in audible beeper
- Display the reader status with LED indicator
- DIP switch
- RS485 and Wiegand(W26/W34) protocol
- Tamper-proof alarm
- Online upgrade function(under the 485 communication mode), and card reader can degrade to pre-upgrade status in case of upgrading failed
- Dust-proof and water-proof design

| Model No. | VIS-3103 |
|---------------------|---|
| Power Supply | 12V DC |
| Working Current | ≤500mA |
| Processor | 32-bit |
| Reading Frequency | 13.56MHz |
| Reading Range | 30 to 50mm (1.18 to 1.96in.) |
| ID Settings | Setting by the DIP Switch on the Main Board |
| Audio Alert | Beeper |
| Power Consumption | ≤6W |
| Certifications | FCC, CE |
| LED Indicator | Power Indicator; Status LED Indicator |
| Working Temperature | -40°C to +70°C (-40°F to +158°F) |
| Working Humidity | 10% to 90% (Non Condensing) |
| Protection Level | IP 64 |
| Dimensions | 132.0L × 92.3W × 20.5P (mm) - 5.20L × 3.63W × 0.81P (in.) |
| Weight | ≤ 0.14Kg (0.30 pounds) |
| Keypad | Keypad with 12 Keys (0 to 9, *, #) |



Disclaimer: VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com