



The VIS-3004 Model is a standard size model with metal keys for industrial locations. This elegant design allows you to have a very good looking Keypad/Reader at your location.

## Features

- 2000 users.
- Aluminum alloy structure, waterproof, IP65. Touch panel.
- Built-in 125KHz (EM card) and 13.56MHz (IC, CPU card, ISO14443A) reader.
- Anti tamper, anti-vandal, antistatic 15KV
- Digital backlit key. The back light can be set to Normal ON, Normal OFF or Automatic mode.
- Door bell function.
- Multi-function, can be used as reader; single door controller, anti-pass back, etc.

Modelo No.	VIS-3004
Input Voltage	DC12~24V
Idle Current	≤35mA
Proximity Card	EM
Reading Range	EM card: 3 - 6cm (1.18 - 2.36 in.) IC&CPU card: 2 - 6cm (0.78 – 2.36 in.)
Frequency	125KHz and 13.56MHz
Wiegand Input & Output Format	26-37 bit
Keypad Output Format	Visual card No; 4 bits or 8 bits of single key pressing
Dimensions	125Lx83Wx21.7H (mm) - 4.92Lx3.26Wx0.85H (in.)
Operating Temperature	-40~60°C (-40~140°F) (EM card), -20~60°C (-4~140°F) IC or CPU card)
Operating Humidity	0~95% (non-condensing)



**Disclaimer:** VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



[sales@visionistech.com](mailto:sales@visionistech.com)



[www.visionistech.com](http://www.visionistech.com)