






## Specifications

- Size: 114Lx70Wx25.7H(mm) / 4.49Lx2.75Wx1.01H (in.)
- Input : DC12V
- Contact rating: 1A@30VDC, 0.5A@125VAC
- Output contact: NO\NC\COM
- Mechanical life: 1,000,000 tests
- Suitable for door: Hollow Door
- Detection range: 4-10cm (1.57-3.93in.) (Adjustable)
- Time delay: 0.5~25s (Adjustable)
- Operating temp: -20°C~+55°C(14°F~131°F)
- Suitable humidity: 0-95% (relative humidity)
- White LED indicator: Power OFF
- Red LED indicator: Power ON (standby)
- Green LED indicator: Power ON (sensation)
- Material: Stainless
- Weight: 0.2kg (0.44 pounds)

## Installation & Size




## Illustration

Detection range: 4-10cm (Adjustable)

VR1 illustration:

- ⊗ The Farthest distance
- ⊕ The Nearest distance



Time delay: 0.5S~25S

VR2 illustration:

- ⊗ Min.time delay
- ⊕ Max.time delay



**Disclaimer:** VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com