



Features

- Innovative LED Design
- 2.5mm or 0.1 Inches ultra-thin, an ideal choice for door access control for office building, households, etc.
- Long Mechanical Life, exceed 1 million times
- Simple installation

Packing List

- 1 × VIS-7005
- 1 × User Manual
- 2 × Rubber Bungs (6 x 24 mm) or (0.2 x 0.9 Inches)
- 2 × Self tapping Screw (3 x 20mm) or (0.1 x 0.7 Inches)
- 1 × Screw Driver
- 4 × Wire (2 X Yellow, 1 X Red, 1 X Black)
- 1 × Install Template Sticker

Model No.	VIS-7005
Mechanical Life	Exceed 1million times
LED Light Color	White
Panel Material	Aluminium Alloy & PC
Button Material	Chromium-Plated Brass
Electrical Ratings	Contact Resistance: ≤60mΩ Insulation Resistance: ≥1000MΩ LED Power: ≤22W Switch Rating: 250V AC LED Supply Power Voltage: 12V DC
Operating Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Dimension	90Hx40Wx2.5D (mm) - 3.54Hx1.57Wx0.1D (in.)
Weight	50g



Disclaimer: VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com